



**1 FLOOR PLAN**  
SCALE: 1/4"=1'-0"



**GENERAL FLOOR PLAN NOTES**

NOTE #1: ALL CONSTRUCTION TO COMPLY WITH APPLICABLE BUILDING CODES, DEED RESTRICTIONS, AND RELATED REGULATIONS.

NOTE #2: BRING ALL ERRORS, OMISSIONS, AND DISCREPANCIES TO THE ATTENTION OF THE ARCHITECT/DESIGNER.

NOTE #3: NOTIFY THE DESIGNER/ARCHITECT IN THE EVENT OF INCONSISTENCIES BETWEEN ACTUAL FIELD CONDITIONS AND THE CONSTRUCTION DOCUMENTS.

NOTE #4: ALL CEILING HEIGHTS TO BE A MIN. OF 10'-0" UNLESS OTHERWISE NOTED.

NOTE #5: ALL ELLIPTICAL ARCH'S OPENINGS TO BE A MIN. OF 8'-0" AFF. \* TOP OF ARCH W/ A SPRING HGT. OF 6" FOR EVERY 36" OF WIDTH UNLESS OTHERWISE NOTED.

NOTE #6: ALL ROOF OVERHANGS AS FOLLOWS: 12" AT ALL DORMERS & 12" GABLE FRONTS AND 18" AT ALL EXTENDED EAVES, AND 12" AT ALL OTHER LOCATIONS (SEE ROOF PLAN)

NOTE #7: VERIFY THAT REQUIRED WINDOWS AND DOORS MEET ALL APPLICABLE CODES.

NOTE #8: ALL GLASS LITES ARE TO BE HIGH PERFORMANCE INSULATED GLASS.

NOTE #9: THE WINDOW AND DOOR SELECTIONS ARE GENERIC. THE CONTRACTOR AND SUPPLIER SHALL VERIFY THAT ALL WINDOW AND DOOR SIZES AND TYPES MEET THE DESIGN INTENT AND PROVIDE A SCHEDULE TO THE ARCHITECT FOR REVIEW AND APPROVAL.

NOTE #10: ALL WINDOWS THAT HAVE JAMBS WITHIN 2'-0" OF ANY DOOR STRIKE (JAMB) & ANY WINDOW SEAL LESS THAN 54" ABOVE THE NEAREST STAIR TREAD/LANDING OR ALL WINDOWS ABOVE TUBS & SHOWERS SHALL BE 'TEMPERED'. CONSULT WINDOW REP. FOR CODE REQUIREMENTS (94-UBC)

NOTE #11: LOCATE KITCHEN COOKTOP VENTHOOD EXHAUST FAN MOTOR IN THE ATTIC.

NOTE #12: LOCATE SHOWER HEADS AT 1'-0" AFF UNLESS NOTED OTHERWISE ON THE PLANS.

NOTE #13: SLEEVE ALL COPPER PIPE PENETRATIONS THROUGH CONCRETE SLABS OR WALLS.

NOTE #14: FRAMER TO VERIFY ROUGH OPENINGS OF ALL APPLIANCES & FIRE PLACE OPENINGS PER MANUFACTURER'S SPECIFICATIONS.

NOTE #15: VENT CLOTHES DRYER TO OUTSIDE IN ACCORDANCE WITH APPLICABLE CODES.

NOTE #16: SEAL ALL SILL PLATES

NOTE #17: PLATE 'WALL' HEIGHTS ARE REFERENCED ON THE ROOF PLAN AND THE ELEVATIONS. THEY ARE TO BE COORDINATE WITH THE EAVE AND RAKE DETAILS.

NOTE #18: LOCATION AND SIZE REQUIREMENTS FOR HVAC DUCT CHASES TO BE VERIFIED BY HVAC SYSTEM DESIGNER. COORDINATE THE LOCATION OF NEW OR LARGER CHASES WITH THE ARCHITECT/DESIGNER.

NOTE #19: UNLESS SHOWN ON PLANS, HVAC AND WATER HEATER LOCATION AND SERVICE REQUIREMENTS TO BE DETERMINED BY OTHERS.

NOTE #20: FOAM SEAL ALL INTERIOR AND EXTERIOR WALL CAVITY OPENINGS, IE. HOSE BIBBS, ELECTRICAL BOXES, ETC.

NOTE #21: PROVIDE SOLID LUMBER BLOCKING IN WALL FOR MISCELLANEOUS FIXTURES AND HARDWARE, IE. TOWEL BARS, CLOSET SHELVEING, CABINETS, CEILING FANS, ETC., WHERE SUCH FIXTURES ARE INDICATED ON THE PLANS.

NOTE #22: FOR DIMENSIONING PURPOSES:  
A: DO NOT SCALE DRAWINGS  
B: ALL INTERIOR WALLS ARE 2X6 & 2X4 STUDS DIMENSIONED TO ONE FACE OF STUD AT 5 1/2" / 3 1/2" TYP. (2X4 AT 2ND FLR. AT 3 1/2") 2X6 AT ALL PLUMBING WALLS  
C: STRUCTURAL WALLS W/ 2X4 STUDS AT 16" O.C. ARE ACCEPTABLE ONLY TO A HEIGHT OF 12 FEET. 2X4 STUD WALLS EXCEEDING 12 FEET IN HEIGHT WILL REQUIRE STRUCTURAL ANALYSIS TO VERIFY STUD SPACING AND/OR ADDITIONAL BRACING.  
D: EXTERIOR MASONRY WALLS ARE AS FOLLOWS:  
2X4'S: 9" FACE OF MASONRY TO FACE OF STUD.  
2X6'S: 11" FACE OF MASONRY TO FACE OF STUD.

**BEDROOM EGRESS WINDOWS**

MINIMUM 5.7 SF. OPENABLE AREA  
MAXIMUM 44 INCH'S SILL HEIGHT  
MINIMUM 20 INCH'S CLEAR WIDTH  
MINIMUM 24 INCH'S CLEAR HEIGHT

**LEGEND**

- DENOTES 2X6 INTERIOR 4 PERIMETER STUD WALL (W/ MASONRY)
- DENOTES 2X4 INTERIOR WALL

**WINDOW SCHEDULE**

SYMBOL	WIDTH	HEIGHT	TYPE	NOTES
A	4'-0"	5'-0"	FIX	36" AFF
B	3'-6"	7'-0"	SH	12" AFF
C	3'-0"	7'-0"	SH	12" AFF
D	3'-0"	7'-0"	SH	24" AFF
E	3'-0"	6'-0"	SH	24" AFF
F	4'-0"	1'-0"	SH	84" AFF
G	3'-0"	5'-0"	SH	24" AFF
H	2'-0"	4'-0"	SH	48" AFF
I	1'-6"	3'-0"	FIX	17'-0" AFF, SEE FRONT ELEV.
J	1'-6"	3'-0"	FIX	5'-6" AFF, AT DORMER
K	3'-0"	6'-0"	SH	24" AFF, SEG. ARCH TOP
L	3'-0"	6'-0"	SH	24" AFF, ARCH TOP
M	1'-0"	7'-0"	FIX	12" AFF, SIDELITE

**DOOR SCHEDULE**

SYMBOL	WIDTH	HEIGHT	TYPE	DESCRIPTION
1	3'-0"	8'-0"	SC	FRONT DOOR
2	3'-0"	8'-0"	SC	1 HOUR FIRE RATED
3	3'-0"	8'-0"	SC	EXTERIOR FRENCH
4	2'-6"	8'-0"	SC	EXTERIOR FRENCH
5	3'-0"	8'-0"	HC	FR 1/6' DOORS
6	3'-0"	8'-0"	HC	-
7	2'-8"	8'-0"	HC	-
8	2'-4"	8'-0"	HC	-
9	2'-0"	8'-0"	HC	-
10	2'-0"	8'-0"	HC	POCKET DOOR

**AREA TABULATIONS**

1st Flr. A/C Area	2,845 sq. ft.
2nd Flr. A/C Area	0 sq. ft.
Bonus Area	0 sq. ft.
Total A/C Area	2,845 sq. ft.
Cvrd. Patio Area	371 sq. ft.
Cvrd. Porch Area	61 sq. ft.
Garage Area	703 sq. ft.
Area Under Roof	3,980 sq. ft.
Gross Slab	3,980 sq. ft.

COPYRIGHT 2021  
THESE DRAWINGS, AS INSTRUMENTS OF SERVICE ARE THE EXCLUSIVE PROPERTY OF THE DESIGNER, AND ARE NOT TO BE USED IN WHOLE OR PART WITHOUT HIS EXPRESS WRITTEN PERMISSION. UNAUTHORIZED USE OF THESE DRAWINGS WILL SUBJECT THE USER TO LEGAL REMEDY BEING SOUGHT BY THE DESIGNER.

THESE ARCHITECTURAL DRAWINGS HAVE BEEN PREPARED FOR ARCHITECTURAL DESIGN ONLY. CIVIL, STRUCTURAL, MECHANICAL, AND OTHER RELATED ENGINEERING DESIGN AND SPECIFICATIONS ARE THE RESPONSIBILITY OF THE RESPECTIVE ENGINEERS. COMPLIANCE TO THESE DRAWINGS WILL BE THE RESPONSIBILITY OF THE GENERAL CONTRACTOR. ALL MEASUREMENTS SHALL BE VERIFIED BY THE CONTRACTORS DOING THE RESPECTIVE WORK.

SCALE: 1/4"=1'-0"  
PROJECT NO. RC2603R1.4.1  
DATE: 3/4/2021  
DESIGNER: MITT  
PROJECT: 3101 DAKOTA DRIVE LOT. 30, BLOCK: C - STARDUST RANCH, PHASE II AN ADDITION TO THE TOWN OF NORTHLAKE, DENTON COUNTY, TEXAS  
Royal Crest Custom Homes

Design Consultants Inc. RESIDENTIAL & COMMERCIAL DESIGNERS - SPACE PLANNING 771 E. SOUTHLAKE BLVD. STE 213 - SOUTHLAKE, TEXAS VOICE (817) 905-7374 - FAX (682) 323-3090